

(11) Utility model Number: 397

(24) Registration date: 12/10/2022

## (12) UTILITY MODEL

(21) Application Number: 2022/1937

(22) Filing Date: 03/08/2022

(73) Owner:

JOMO KENYATTA UNIVERSITY OF AGRICULTURE AND TECHNOLOGY of P. O. BOX 62000-00200 NAIROBI, Kenya

(72) Inventors:

GICHUKI JOYLINE, P. O. BOX 62000-00200 NAIROBI, KENYA; PATRICK GACHOKI KARERU, P. O. BOX 62000-00200, NAIROBI, KENYA; ANTHONY GACHANJE, P. O. BOX 62000-00200 NAIROBI, KENYA; NGAMAU CATHERINE, P. O. BOX 62000-00200 NAIROBI, KENYA and EDWIN SHIGWENYA MADIVOLI, P. O. BOX 62000-00200 NAIROBI, KENYA

(74) Agent/address for correspondence: DIRECTORATE OF INTELLECTUAL PROPERTY MANAGEMENT AND UNIVERSITY-INDUSTRY LIAISON JKUAT, P. O. BOX 62000 - 00200, NAIROBI, KENYA

Int.Cl.2016.01: B 01J 20/24, C 08B 15/02, A 23L 33/24, A 61K 8/73

(54) Title: METHOD OF EXTRACTING MICROCRYSTALLINE CELLULOSE FIBERS FROM

(57) Abstract:

The present invention relates to a method of producing microcrystalline cellulose, and in particular a method of extracting microcrystalline cellulose from coir fibers. Coir fiber is an agricultural feedstock that has been neglected and can now be used to produce microcrystalline cellulose. The method of extracting microcrystalline cellulose fiber from coir fibers is characterized in that the it comprises following steps: Preparing the sample, extracting cellulose from the dried biomass/coir, and Converting cellulose to microcrystalline cellulose. The conversion to microcrystalline cellulose involves treat cellulose with 2.5 N hydrochloric acid at 85°C for 15 min followed by washing with ethanol (10% v/v) then drying in an oven set at 105°C to constant weight. The microcrystalline cellulose is industrially applicable in the binder, pharmaceutical, and paper making industries.